

Brady Standart RFID Labels

Material reference	L-2899-4C	L-2588-19A	L-2588-26B	L-2588-26C	L-2899-8A	L-2899-7B	L-2588-25C	L-2588-25B	L-2588-27C	L-2588-27D
Label reference	THT-UHF-B481-24x16	THT-UHF-B7425-45x30	THT-UHF-B7425-53x26	THT-UHF-B423-53x26	THT-UHF-B423-93x26	THT-NFC-B423-50x40	THT-UHF-64x6	THT-NFC-25x25	THT-UHF/HF-B423-66x46	THT-UHF/HF-B423-33x17
Art number	309083	309082	309081	307923	309085	309084	309087	309086	310251	310250
Markets	Laboratory	General Laboratory Manufacturing Healthcare	General Laboratory Manufacturing Healthcare Transport & Logistics	General Manufacturing Healthcare Transport & Logistics	General Manufacturing Warehousing	General Manufacturing	General Manufacturing Healthcare Data/Telecom	General Manufacturing Healthcare	General Laboratory Manufacturing Healthcare Data/Telecom Transport & Logistics	General Laboratory Manufacturing Healthcare Data/Telecom Transport & Logistics
Application	Medical slide labelling	Product ID & Product life cycle ID Specimen & Laboratory labelling Large conical bottles, tubes and well plates	Product ID & Product life cycle ID Specimen & Laboratory labelling Large conical bottles, tubes and well plates Medical equipment ID Distribution & Warehousing	Product ID & Product life cycle ID Medical equipment ID Distribution & Warehousing	Temperature monitoring	Temperature monitoring	On-metal ID	On-metal ID	Product ID & Product life cycle ID Specimen & Laboratory labelling Medical equipment ID Distribution & Warehousing	Product ID & Product life cycle ID Specimen & Laboratory labelling Medical equipment ID Distribution & Warehousing
RFID type	UHF	UHF	UHF	UHF	UHF	NFC	UHF	NFC	NFC + UHF	NFC + UHF
Material	Polyester (B-481)	Polypropylene (B-7425)	Polypropylene (B-7425)	Polyester (B-423)	Polyester (B-423)	Polyester (B-423)	Polyester	Polyester	Polyester (B-423)	Polyester (B-423)
Read range	Up to 2m	Up to 6m	Up to 10m	Up to 11m	Up to 9m	Up to 5cm	Up to 3m	Up to 2cm	Up to 5m (UHF) Up to 2 cm (NFC)	Up to 2.8m (UHF) Up to 2 cm (NFC)
Dimensions	24 x 16 mm	45 x 30 mm	53 x 26 mm	53 x 26 mm	93 x 26 mm	50 x 40 mm	64 x 6 mm	25 x 25 mm	66 x 46 mm	33 x 17 mm
EPC memory	128 bits	448 bits	128 bits	128 bits	128 bits	/	128 bits	/	128 bits	480 bits
User vmemory	512 bits	2048 bits	/	/	176 bits	320 bytes	/	144 bytes	160 bits (UHF), 1920 bits (NFC)	2048 bits (UHF, HF)
Qty/roll	500	500	500	500	500	500	500	500	500	500
Operating temperature	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-35 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C

All standard RFID labels are fully customisable, including antennas, chips, sensor, label material, adhesive and print.

